



art metal

F.P.H. Art Metal Sp.j.

Ul. Jabłoniowa 124, 83-331 Łapino Kartuskie, Poland

Tel. 0048 58 681 80 78, Fax: 0048 58 681 80 64

www.art-metal.pl e-mail: biuro@art.-metal.pl

POLE KXX - Catalogue card

Construction:

1. Masking frame - cast iron.
2. Fastening disk - steel.
3. Steel pipe $\varnothing 114$.
4. Flute pipe $\varnothing 160$ - cast aluminium .
5. Flute pipe (cone) - cast aluminium.
6. Reducing ring - cast aluminium.
7. Top - cast aluminium.
8. Inspection door.
9. Grounding bolt.

General information:

Pole	Standard height	Final diameter	Foundation	Maximum weight
KXX	3125 mm	$\varnothing 89$	F100A	75,5 kg

The top of the pole depends on a luminary or a head.
Maximum height of the lantern - 5,5 m.

Pole finish:

- galvanizing of steel elements according to PN-EN ISO 1461
- wet coating, multilayer according to PN-EN ISO 8501-1
- standard colour RAL7021, RAL 9005, all other RAL palette colours as an option

Load capacity:

- maximum wind area for a standard pole: 1,2 m²
- capacity for the wind area I (V = 22 m/s), II terrain category, according to PN - EN 40-3-1, PN - EN 40-3-3



Pole fastening:

4xM16
150x150

